

MARITIME APPLICATION QUESTIONNAIRE

The details of the questionnaire serve as a basis of the quotation, the project planning and the order confirmation.
Please fill in the following questions completely

Customer

| | | | | | |
|-----------|-----------------------------------|---------------------------------|-------------------------------------|-------------------------------------|-----------------------------------|
| Company: | <input type="text"/> | | | Date: | <input type="text"/> |
| Address: | <input type="text"/> | | | | |
| Address: | <input type="text"/> | | | | |
| ZIP code: | <input type="text"/> | Location: | <input type="text"/> | | |
| Country: | <input type="text"/> | | | | |
| Web site: | <input type="text"/> | | | | |
| Name: | <input type="text"/> | | | | |
| E-mail: | <input type="text"/> | | | | |
| Phone: | <input type="text"/> | | | | |
| Function: | <input type="checkbox"/> Engineer | <input type="checkbox"/> Sales | <input type="checkbox"/> Purchasing | <input type="checkbox"/> Other: | <input type="text"/> |
| Cluster: | <input type="checkbox"/> Scrubber | <input type="checkbox"/> SCR | <input type="checkbox"/> Engine | <input type="checkbox"/> Integrator | <input type="checkbox"/> Shipyard |
| | <input type="checkbox"/> Owner | <input type="checkbox"/> Other: | <input type="text"/> | | |

Project

| | | | | | | |
|-----------------|---|--------------------------------------|--|------------------------------------|---------------------------------|-------------------------------------|
| Vessel: | Name: <input type="text"/> | IMO no: <input type="text"/> | Gross-Tonnage (GT): <input type="text"/> | | | |
| | Building no: <input type="text"/> | Yard: <input type="text"/> | Flag state: <input type="text"/> | Class: <input type="text"/> | | |
| Type of vessel: | <input type="checkbox"/> Ferry | <input type="checkbox"/> Cruise-ship | <input type="checkbox"/> Bulker | <input type="checkbox"/> Container | <input type="checkbox"/> Tanker | <input type="checkbox"/> LNG Tanker |
| | <input type="checkbox"/> Multi-Purpose-Vessel (MPV) | <input type="checkbox"/> Other: | <input type="text"/> | | | |
| Operating area: | <input type="checkbox"/> ECA | <input type="checkbox"/> Non ECA | <input type="checkbox"/> Detail: | <input type="text"/> | | |

MARPOL Compliance

| | | | | | | |
|---------------|--|---|--|--|--------------------------------------|---------------------------------|
| Compliance: | <input type="checkbox"/> LSF (<0.1% S) | <input type="checkbox"/> Fuel switching | <input type="checkbox"/> LNG | <input type="checkbox"/> Exhaust Gas Cleaning system (EGCS) | | |
| Applied Reg.: | <input type="checkbox"/> MEPC.184(59) scheme A | | <input type="checkbox"/> MEPC.184(59) scheme B | <input type="checkbox"/> NO _x monitoring acc. to NTC 2008 | | |
| | <input type="checkbox"/> Other: <input type="text"/> | | | | | |
| EGCS aboard: | <input type="checkbox"/> No scrubber | <input type="checkbox"/> Dry scrubber | <input type="checkbox"/> Wet scrubber | <input type="checkbox"/> Open loop | <input type="checkbox"/> Closed loop | <input type="checkbox"/> Hybrid |
| | <input type="checkbox"/> SCR | <input type="checkbox"/> Other: | <input type="text"/> | | | |
| | Type and brand of EGCS: <input type="text"/> | | | | | |

Application

| | | | | | | | | | |
|-----------------------------|--|---|--|------------------------------------|--|---|-----------------------------|--|--|
| Sample point(s): | <input type="checkbox"/> Before scrubber | <input type="checkbox"/> After scrubber | <input type="checkbox"/> Before SCR | <input type="checkbox"/> After SCR | <input type="checkbox"/> No EGCS | | | | |
| Gas components: | <input type="checkbox"/> SO _{2,low} | <input type="checkbox"/> SO _{2,high} | <input type="checkbox"/> CO ₂ | <input type="checkbox"/> NO | <input type="checkbox"/> NO ₂ | <input type="checkbox"/> O ₂ | <input type="checkbox"/> CO | <input type="checkbox"/> CH ₄ | <input type="checkbox"/> NH ₃ (Note: SO _{2,high} , NH ₃ and CH ₄ only MARSIC300) |
| Others: | <input type="checkbox"/> PM | <input type="checkbox"/> Gas fuel flow | <input type="checkbox"/> Exhaust flow | <input type="checkbox"/> Other: | <input type="text"/> | | | | |
| Measuring points: | <input type="checkbox"/> 1 | <input type="checkbox"/> 2 | <input type="checkbox"/> 3 | <input type="checkbox"/> 4 | <input type="checkbox"/> 5 | <input type="checkbox"/> 6 | <input type="checkbox"/> 7 | <input type="checkbox"/> 8 | |
| Preferred no. of analyzers: | <input type="checkbox"/> 1 | <input type="checkbox"/> 2 | <input type="checkbox"/> 3 | <input type="checkbox"/> 4 | | | | | |
| Notes: | <input type="text"/> | | | | | | | | |

(e.g.: two analyzers needed because of distance of stacks ... located at gallery after scrubber beside engine room ...)

Power and auxiliaries supplies

| | | | | |
|---------------|--|---|---|--|
| Power Supply: | <input type="checkbox"/> 115 V AC | <input type="checkbox"/> 230 V AC | <input type="checkbox"/> 400 V AC | <input type="checkbox"/> Other: <input type="text"/> |
| | <input type="checkbox"/> 1 Phase | <input type="checkbox"/> 2 Phases | <input type="checkbox"/> 3 Phases | |
| | <input type="checkbox"/> N available | <input type="checkbox"/> PE available | | |
| | <input type="checkbox"/> 50 Hz | <input type="checkbox"/> 60 Hz | | |
| Air supply: | <input type="checkbox"/> Not available | <input type="checkbox"/> Available, flow >100 l/h | <input type="checkbox"/> Available, flow >1.300 l/h | Pressure: <input type="text"/> bar |
| Air quality: | <input type="checkbox"/> P. -size < 1 µm | <input type="checkbox"/> Content of oil max. 0.1 mg/m ³ | <input type="checkbox"/> Pressure condensation point below -30 °C | |
| | <input type="checkbox"/> Unknown | <input type="checkbox"/> Instrument air conditioning unit (option) needed (strongly recommended, in MARSIC300 included) | | |

Site of Equipment Installation (Analyzer)

| | | | |
|--------------------------|--|----------------------------------|--|
| Location: | <input type="checkbox"/> Engine room | <input type="checkbox"/> Stack | <input type="checkbox"/> Other: <input type="text"/> |
| Amb. conditions: | <input type="checkbox"/> Indoor | <input type="checkbox"/> Outdoor | <input type="checkbox"/> Air conditioned location |
| Amb. temp: | Min.: <input type="text"/> °C <small>(Use certified range 5 °C ... 45 °C)</small> | Max.: <input type="text"/> °C | Typical: <input type="text"/> °C |
| Weather proof required: | <input type="checkbox"/> No | <input type="checkbox"/> Yes | |
| Description of location: | <input type="text"/> | | |

(e.g.: gallery after scrubber on D-deck beside the SCR (distance to measuring point A~15 m, to measuring point B: 5 m; within starboard exhaust stack ...)

| Sampling points | Point 1 | Point 2 | Point 3 | Point 4. |
|--|--|--|--|--|
| Location: | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Weather proof required: | <input type="checkbox"/> No <input type="checkbox"/> Yes |
| Ambient air temp (min-max): <small>(Use certified Range 5 °C ... 45 °C)</small> | <input type="text"/> °C | <input type="text"/> °C | <input type="text"/> °C | <input type="text"/> °C |
| Inner stack diameter at sampl. point: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Wall thickness | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Insulation width | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |
| Sample probe length required: | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm | <input type="text"/> mm |

Sampling transport

| | | | | |
|---|--|--|--|--|
| Distance sample probe to analyzer: <small>(Including at least 2 m additionally length for bending)</small> | <input type="text"/> m | <input type="text"/> m | <input type="text"/> m | <input type="text"/> m <small>For MARSIC200 both lengths: (hot / cold)</small> |
| Measuring gas return: | <input type="checkbox"/> No <input type="checkbox"/> Yes |
| Length of return path: <small>(Including at least 2 m additionally length for bending)</small> | <input type="text"/> m | <input type="text"/> m | <input type="text"/> m | <input type="text"/> m |
| Backpressure: | <input type="text"/> hPa | <input type="text"/> hPa | <input type="text"/> hPa | <input type="text"/> hPa |

Sample Gas Conditions

| | | | | |
|----------------------------|--|--|--|--|
| Gas/operating temperature: | <input type="text"/> °C | <input type="text"/> °C | <input type="text"/> °C | <input type="text"/> °C |
| Gas/operating pressure: | <input type="text"/> hPa | <input type="text"/> hPa | <input type="text"/> hPa | <input type="text"/> hPa |
| Max. expected humidity: | <input type="text"/> %-rel. | <input type="text"/> %-rel. | <input type="text"/> %-rel. | <input type="text"/> %-rel. |
| Dust/solid content: | <input type="text"/> mg/m ³ |

Measuring system

| | | | | | |
|--|--|---|--|---|---|
| Preferred technology: | <input type="checkbox"/> Hot/wet | <input type="checkbox"/> Cold/dry | <input type="checkbox"/> No preferences | | |
| Preferred modularity: <small>(For details see sketches on page 3)</small> | <input type="checkbox"/> Compact (1 housing, MARSIC300) | <input type="checkbox"/> Modular (3 housings, MARSIC200) | <input type="checkbox"/> No preferences | | |
| Adjustment: | <input type="checkbox"/> Calibration-gas prefer. | <input type="checkbox"/> Calibration check tool preferred | <input type="checkbox"/> No preferences | | |
| Additional options (future): | <input type="checkbox"/> NH ₃ | <input type="checkbox"/> CH ₄ | <input type="checkbox"/> SO _{2, high} | <input type="checkbox"/> Additional sampling points | <input type="checkbox"/> No preferences |
| Redundancy needed: | <input type="checkbox"/> No | <input type="checkbox"/> Yes | | | |
| Sampling line: <small>(For details see sketches on page 3)</small> | <input type="checkbox"/> Long distance line should be "cold" (sampl. point -> short heated line -> sampling preparation unit -> long cold line to analyzer) <input type="checkbox"/> Complete line from sampling point to analyzer should be "hot" (sampling point -> heated line to analyzer) <input type="checkbox"/> No preferences | | | | |
| Halogens reduced set up needed: | <input type="checkbox"/> No | <input type="checkbox"/> Yes | | | |

Data Handling

Interface used: AO DO Modbus TCP Modbus RTU PROFIBUS OPC Other:

Connectivity to board systems: No Yes, using:

Data Acquisition required No Yes, main specs:

Maintenance

Maintenance performed: During sailing In port In yard

Maintenance performed: Crew/engineer Scrubber manufacturer Engine manufacturer Service organization

Other:

Preferred Berth for installation / service: No Yes:

Interested in SICK Service: No Yes, extent of services:


Interested in installation/ commissioning: No Yes

Service Package & Spare

Service kits needed: "Standard" (includes everything for the "first aid" aboard (fuses, filters, water trap, leak test kit, etc.)
 "Advanced" (includes "Standard" as well as measuring modules (DeNO_x/DeSO_x, etc.)

Notes

Sketches MARSIC200 + MARSIC300



Cable Configuration MARSIC200

